

## iQ500, Canopy cooker hood, 70 cm, Stainless steel LB78574GB

C



The powerful canopy cooker hood is concealed in a unit above the hob.

✓ LED lights: for optimal visibility and ambience while cooking.

### Features

#### Technical Data

Typology : Built-in/Built-under  
 Approval certificates : CE, VDE  
 Length of electrical supply cord : 150 cm  
 Required niche size for installation (HxWxD) : 418mm x 676.0mm x 264mm mm  
 Minimum distance above an electric hob : 500 mm  
 Minimum distance above a gas hob : 650 mm  
 Net weight : 8.963 kg  
 Type of control : Electronic  
 Maximum output air extraction : 630 m<sup>3</sup>/h  
 Boost position output recirculating : 664 m<sup>3</sup>/h  
 Maximum output recirculating air : 571 m<sup>3</sup>/h  
 Boost position air extraction : 730 m<sup>3</sup>/h  
 Number of lights (Stck) : 2  
 Noise level : 66 dB(A) re 1 pW  
 Diameter of air outlet : 120 / 150 mm  
 Grease filter material : Washable aluminium  
 EAN code : 4242003686263  
 Connection rating : 277 W  
 Fuse protection : 3 A  
 Voltage : 220-240 V  
 Frequency : 50 Hz  
 Plug type : GB plug  
 Installation type : Built-in



### Optional accessories

LZ55750	Standard recirculation kit
LZ55651	Standard odor filter (replacement)
LZ11IXC16	Clean Air Plus recirc. kit external
LZ11IXB16	Clean Air Plus odor filter (replacement)
LZ11ITD11	Long Life recirculation kit external

## iQ500, Canopy cooker hood, 70 cm, Stainless steel LB78574GB

### Features

#### Key Information

- Soft touch button control for extractor speeds and light
- 3 x power levels plus intensive setting
- Automatic intensive revert (6mins)
- 2 x 1W LED lights
- 2 x metal grease filter cassettes
- Steel filter cover, Steel filter cover
- Rim ventilation

#### Design

- 70 cm wide
- Stainless Steel
- Installation: Cabinet
- Electronic control via Soft touch button control
- White electronic display

#### Performance/technical information

- Suitable for ducted and re-circulating operation
- For recirculated extraction recirculating kit or CleanAir recirculating kit (accessory) needed
- Extraction rate according to EN 61591  $\varnothing$  15 cm:
  - max. Normal use 630 m<sup>3</sup>/h
  - Intensive 730 m<sup>3</sup>/h
- Noise level according to EN 60704-3 and EN 60704-2-13 exhaust air:
  - Max. normal use: 66 dB(A) re 1 pW
  - Intensive: 69 dB(A) re 1 pW
- With the Clean Air Plus recirculation kit (available as optional accessory) your appliances reaches:
  - Extraction rate in recirculation mode:
    - Max. normal use: 571 m<sup>3</sup>/h
    - Intensive: 664 m<sup>3</sup>/h
  - Noise level in recirculation mode:
    - Max. normal use: 72 dB(A) re 1 pW
    - Intensive: 75 dB(A) re 1 pW
- Power rating: 277 W
- Light Intensity: 244 lux
- Colour Temperature: 4000 K
- Dimensions (WxD): 700 x 300 mm
- Built-in dimensions (HxWxD): 418 x 676 x 264 mm
- Dimensions exhaust air (HxWxD): 418-418 x 700 x 300 mm
- Diameter pipe  $\varnothing$  150 mm ( $\varnothing$  120 mm enclosed)
- Average Energy Consumption: 104.2 kWh/year\*
- Energy Efficiency Class: C (at a range of energy efficiency classes from A+++ to D)
- Blower Efficiency Class: C\*
- Lighting Efficiency Class: A\*
- Grease Filtering Efficiency Class: D\*

\* In accordance with the EU-Regulation No 65/2014

iQ500, Canopy cooker hood, 70 cm,  
Stainless steel  
LB78574GB

Dimensioned drawings

