

N 30, Wall-mounted cooker hood, 60 cm, clear glass
D64GBCON0B



A

The flat glass canopy hood accentuates the box hood design with a mix of modern materials and straight lines.

- ✓ LED Lighting – Clear illumination while you cook.
- ✓ High Extraction Rate – ensures a clear view while cooking thanks to an efficient motor technology

Features

Technical Data

Typology : Wall-mounted
 Approval certificates : CE, E17D UKCA marking, VDE
 Length of electrical supply cord : 130 cm
 Height of the chimney : 576-906/576-998 mm
 Height of product, without chimney : 59 mm
 Minimum distance above an electric hob : 550 mm
 Minimum distance above a gas hob : 650 mm
 Net weight : 13.461 kg
 Type of control : mechanical
 Number of speed settings : 3
 Maximum output air extraction : 650 m³/h
 Maximum output recirculating air : 422 m³/h
 Number of lights (Stck) : 2
 Noise level : 70 dB(A) re 1 pW
 Diameter of air outlet : 120 / 150 mm
 Grease filter material : Washable aluminium
 EAN code : 4242004224051
 Connection rating : 220 W
 Fuse protection : 10 A
 Voltage : 220-240 V
 Frequency : 50; 60 Hz
 Plug type : GB plug
 Installation type : Wall-mounted



4 242004 224051

Optional accessories

Z51DXA0X0	Standard odor filter (replacement)
Z51DXI1X6	Clean Air Plus recirculation kit
Z51DXU0X0	Standard recirculation kit
Z51FXC1N6	Clean Air Plus recirc. kit external
Z51FXJ0X0	Long Life recirculation kit
Z53XXB1X6	Clean Air Plus odor filter (replacement)
Z5865N0	Stainless steel back panel 600 mm
Z5905N0	Chimney extension 1000 mm
Z5915N0	Chimney extension 1500 mm

N 30, Wall-mounted cooker hood, 60 cm, clear
glass
D64GBCONOB



COOKING PASSION SINCE 1877

Features

Key performance features:

- Energy Efficiency Class: A (at a range of energy efficiency classes from A+++ to D)
- Max. extraction rate: 649 m³/h
- Noise max. Normal Level: Noise, max. speed in normal us: 70 dB dB*

Features

- Push button control operation
- 3 power levels
- 2 x 1.5w LED Light
- Colour Temperature: 3500 K
- 1 metal grease filter cassette
- Installation: wall

Design

- Chimney hood
- Mechanical controls

Performance/technical information

- Suitable for ducted extraction and recirculation
- For recirculated extraction recirculating kit or CleanAir recirculating kit (accessory) needed
- Maximum extraction rate exhaust air 649 m³/h according to EN 61591
- Noise level according to EN 60704-3 and EN 60704-2-13 at max. normal use exhaust air: 70 dB(A) re 1 pW
- Power rating: 220 W
- Light Intensity: 110 lux
- Electrical cable length 1.3 m
- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
- Dimensions exhaust air (HxWxD): 635-965 x 600 x 525 mm
- Dimensions recirculating (HxWxD): 635-1075 x 600 x 525 mm
- Dimensions recirculating with CleanAir module (HxWxD):
703 x 600 x 525 mm - mounting with outer chimney
833-1163 x 600 x 525 mm - mounting with telescopic chimney
- Blower Efficiency Class: A*
- Lighting Efficiency Class: A*
- Grease Filtering Efficiency Class: B*
- Average Energy Consumption: 42.4 kWh/year*

Optional accessories

- Recirculating kit Z50XXP0X0

* In accordance with the EU-Regulation No 65/2014

N 30, Wall-mounted cooker hood, 60 cm, clear glass
D64GBCONOB

Dimensioned drawings

