### N 50, Built-in double oven, Stainless steel J1ACE2HNOB







#### Included accessories

 $2 \times \text{combination grid}, 1 \times \text{universal pan}$ 

#### Optional accessories

Z11AB15A0	Baking tray, non-stick ceramic coated
Z11CB10E0	Baking tray, grey enamelled
Z11CR10X0	Baking and roasting grid (standard)
Z11GT10X3	Glass roasting dish, 5,4l
Z11TI15X0	Cliprails

### Built under double oven - twice as flexible, twice as fast - bake or roast multiple dishes at the same time.

- $\sqrt{}$  EasyClean this special cleaning aid provides uncomplicated, energy-saving cleaning of the oven interior.
- $\sqrt{\rm \ LCD-Display}$  simple, straightforward with large characters for clear reading
- $\checkmark\,$  Clip-on Rail easily removed and installed telescopic rails for flexible use on all shelf levels

#### Features

Technical Data Color / Material Front : Stainless steel Construction type : Built-in Integrated Cleaning system : No Dimensions of the product (mm) : 717 x 594 x 550 Dimensions of the packed product (HxWxD) (mm) :  $790 \times 690 \times 660$ Control Panel Material : Glass Door Material : Glass Net weight (kg) : 47.391 Usable volume of cavity (I) : 47 Cooking method : Conventional heat, Full width grill, Hot Air, Hot air grilling, Pizza setting Oven control : mechanical Number of interior lights : 1 Approval certificates : CE, VDE EAN code : 4242004221982 Energy efficiency class (2010/30/EC) : A Energy consumption per cycle conventional (2010/30/EC) : 0.84 Energy consumption per cycle forced air convection (2010/30/EC) : 0.71 Energy efficiency class (2010/30/EC) - cavity 2 : B Energy consumption per cycle conventional - cavity 2 (2010/30/EC) : 0.83 Energy efficiency index (2010/30/EC) : 94.7 Energy efficiency index cavity 2 (2010/30/EC) : 120.3 Connection rating (W) : 5300 Current (A) : 25 Voltage (V) : 220-240 Frequency (Hz) : 50 Plug type : fixed connection, no plug



## N 50, Built-in double oven, Stainless steel JIACE2HNOB

#### Features

## \* LCD Display (White)Features

- Control panel lock
- Interior halogen light
- Cavity volume: 34 Litre
- Door hinge small cavity: bottom
- Cavity (inner surface) top: Enamel grey
- EasyClean
- Full glass inner door
- 1 Clip rail, Stop function
- Cavity (inner surface) bottom: Enamel grey
- Door hinge big cavity: Drop down door

#### Top oven additional features


- Oven with 4 heating methods: Top/bottom heat, Full surface grill, Small area grill, Bottom heat
- Temperature range 50 °C 275 °C


#### Main oven additional features

- 2 x combination grid, 1 x universal pan
- Performance/technical information
- Nominal voltage: 220 240 V
- Appliance dimension (hxwxd): 717 mm x 594 mm x 550 mm
- Please refer to the dimensions provided in the installation manual

# N 50, Built-in double oven, Stainless steel JIACE2HNOB

#### Dimensioned drawings





measurements in mm If the appliance will be installed underneath a hob, the following worktop thicknesses (including substructure if necessary) must be taken into account.

Hob type	min. worktop thickness	
	fitted	flush
Induction hob	39	40
Full-surface induction hob	49	50
Gas hob	29	40
Electric hob	29	32